

AENOR

ENEC Certification Body registered under ID # 01. For further information, please consult www.enec.com

LICENCE

to use the European Mark



Licence Nr. ENEC/000975

Under the conditions given in the following pages of this document, the licence to use the ENEC Mark in conjunction with the suffix 01, as shown above, has been issued to:

ESPECIALIDADES LUMINOTÉCNICAS, S.A.U.
PI MALPICA, CL E, 11
50016 ZARAGOZA (España Spain)

For the product(s):

Electronic control gear for LED modules

Trade name(s):

ELT

Complying with the following European Standards:

EN 61347-1:2015; EN 61347-2-13:2014;
EN 61347-2-13:2014/A1:2017; EN 62384:2006/A1:2009;
EN 62384:2006

Date: 2018-03-08

Signature:

A handwritten signature in blue ink, appearing to read 'Rafael García', with a stylized flourish at the end.

Name: Rafael García

Position: General Manager

This licence has been issued under the presumption and conditional on the fact that the licensee holds all necessary legal rights with regard to the product presented for testing and certification.

AENOR INTERNACIONAL, S.A.U.
CI Génova, 6
28004 MADRID (Spain)

AENOR

CERTIFICADO ENEC DE PRODUCTO



Tipo de producto / Type of Product	CONTROL ELECTRÓNICO PARA MÓDULOS LED
r1) N° Certificado / Certificate n°	ENEC/000975
r2) Fecha Certificado / Date of the Certificate	2018-03-08
r3) N° de Informe de ensayo / Test report n°	201402130048-M1, 201402130049-M1, 201402130050-M1, 201402130051-M1, 201402130050-M2-A1, 201402130051-M2, 2016050304B1, 201402130051-M3, 201402130050-M3, 2018010013B1-2, 2018010013B1-1
r4) Nombre y dirección del licenciario Name and address of the licensee	ESPECIALIDADES LUMINOTÉCNICAS, S.A.U. PI MALPICA, CL E, 11 50016 ZARAGOZA (España)
r5) Dirección de la factoría Address of the factory	PI MALPICA, CL E NAVE 11 50016 ZARAGOZA (España)
r6) Referencia de la Norma Española Spanish Standard	UNE-EN 61347-1:2016; UNE-EN 61347-2-13:2015; UNE-EN 61347-2-13:2015/A1:2017; UNE-EN 62384:2007/A1:2010; UNE-EN 62384:2007
r7) Referencia de la Norma Europea European Standard	EN 61347-1:2015; EN 61347-2-13:2014; EN 61347-2-13:2014/A1:2017; EN 62384:2006/A1:2009; EN 62384:2006
r8) Referencia / Reference	Ver Anexo I <i>refer to Annex I</i>
r9) Marca Comercial / Trade Mark	ELT
r10) Tensión y frecuencia de alimentación Voltage and frequency supply	Ver Anexo I <i>refer to Annex I</i>
r11) Potencia total y factor de potencia Total power and power factor	Ver Anexo I <i>refer to Annex I</i>
r12) Tensión o corriente de salida estabilizada Voltage or current stabilized output	Ver Anexo I <i>refer to Annex I</i>
r13) Tc máxima / Tc maximum	Ver Anexo I <i>refer to Annex I</i>
r14) Clasificación / Classification	Ver Anexo I <i>refer to Annex I</i>
r15) Apto para regulador de tensión de red Suitable for supply voltage dimmer	Ver Anexo I <i>refer to Annex I</i>
r16) Datos adicionales / Additional data	Ver Anexo I <i>refer to Annex I</i>
Fecha de caducidad: 2021-06-30 Date of expiry	Este certificado anula y sustituye al 007/000975, de fecha 2016-11-11. This certificate supersedes certificate 007/000975, dated 2016-11-11.

AENOR INTERNACIONAL S.A.U.
Génova, 6. 28004 Madrid. España
Tel. 91 432 60 00.- www.aenor.es

Entidad de certificación de producto acreditada por ENAC con n° 01/C-PR275
Product certification body accredited by ENAC, number 01/C-PR275

AENOR

CERTIFICADO ENEC DE PRODUCTO



ANEXO I AL CERTIFICADO ENEC/000975 ANNEX I TO CERTIFICATE ENEC/000975

REFERENCIA <i>Reference</i>	TENSIÓN Y FRECUENCIA DE ALIMENTACIÓN <i>Voltage and frequency supply</i>	POTENCIA TOTAL Y FACTOR DE POTENCIA <i>Total power and power factor</i>	TENSIÓN O CORRIENTE DE SALIDA ESTABILIZADA <i>Voltage or current stabilized output</i>	TC MÁXIMA <i>Tc maximum</i>	CLASIFICACIÓN <i>Classification</i>	APTO PARA REGULADOR DE TENSIÓN DE RED <i>Suitable for supply voltage dimmer</i>	DATOS ADICIONALES <i>Additional data</i>
DLC 137/1200-E-C2-1 ... 10 V	220-240 V-; 0 ... 50/60 Hz	25-37 W; PF: 0,94	Stabilized current: 1200 mA, at 31 V max.	80 °C	Indenpendent	No	Short-circuits withstand; class II; terminals connection; thermal protection at tc = 100 °C; 1-10 V dimming
DLC 137/1200-E-1 ... 10 V	220-240 V-; 0 ... 50/60 Hz	25-37 W; PF: 0,94	Stabilized current: 1200 mA, at 31 V max.	80 °C	To build-in	No	Short-circuits withstand; class I; terminals connection; thermal protection at tc = 100 °C; 1-10 V dimming
DLC 142/1050-E-C2-1 ... 10 V	220-240 V-; 0 ... 50/60 Hz	31-42 W; PF: 0,97	Stabilized current: 1050 mA, at 40 V max.	75 °C	Indenpendent	No	Short-circuits withstand; class II; terminals connection; thermal protection at tc = 100 °C; 1-10 V dimming
DLC 142/1050-E-1 ... 10 V	220-240 V-; 0 ... 50/60 Hz	31-42 W; PF: 0,97	Stabilized current: 1050 mA, at 40 V max.	75 °C	To build-in	No	Short-circuits withstand; class I; terminals connection; thermal protection at tc = 100 °C; 1-10 V dimming
DLC 142/1400-E-C2-1 ... 10 V	220-240 V-; 0 ... 50/60 Hz	31-42 W; PF: 0,96	Stabilized current: 1400 mA, at 30 V max.	80 °C	Indenpendent	No	Short-circuits withstand; class II; terminals connection; thermal protection at tc = 100 °C; 1-10 V dimming
DLC 142/1400-E-1 ... 10 V	220-240 V-; 0 ... 50/60 Hz	31-42 W; PF: 0,96	Stabilized current: 1400 mA, at 30 V max.	80 °C	To build-in	No	Short-circuits withstand; class I; terminals connection; thermal protection at tc = 100 °C; 1-10 V dimming
DLC 142/350-E-C2-1 ... 10 V	220-240 V-; 0 ... 50/60 Hz	24-41 W; PF: 0,96	Stabilized current: 350 mA, at 117 V max.	75 °C	Indenpendent	No	Short-circuits withstand; class II; terminals connection; thermal protection at tc = 100 °C; 1-10 V dimming
DLC 142/350-E-1 ... 10 V	220-240 V-; 0 ... 50/60 Hz	24-41 W; PF: 0,96	Stabilized current: 350 mA, at 117 V max.	75 °C	To build-in	No	Short-circuits withstand; class I; terminals connection; thermal protection at tc = 100 °C; 1-10 V dimming
DLC 142/500-E-C2-1 ... 10 V	220-240 V-; 0 ... 50/60 Hz	24-40 W; PF: 0,96	Stabilized current: 500 mA, at 80 V max.	75 °C	Indenpendent	No	Short-circuits withstand; class II; terminals connection; thermal protection at tc = 100 °C; 1-10 V dimming

Original Electrónico

AENOR INTERNACIONAL S.A.U.
Génova, 6. 28004 Madrid. España
Tel. 91 432 60 00.- www.aenor.es

Entidad de certificación de producto acreditada por ENAC con nº 01/C-PR275
Product certification body accredited by ENAC, number 01/C-PR275

AENOR

CERTIFICADO ENEC DE PRODUCTO



ANEXO I AL CERTIFICADO ENEC/000975 ANNEX I TO CERTIFICATE ENEC/000975

REFERENCIA <i>Reference</i>	TENSIÓN Y FRECUENCIA DE ALIMENTACIÓN <i>Voltage and frequency supply</i>	POTENCIA TOTAL Y FACTOR DE POTENCIA <i>Total power and power factor</i>	TENSIÓN O CORRIENTE DE SALIDA ESTABILIZADA <i>Voltage or current stabilized output</i>	TC MÁXIMA <i>Tc maximum</i>	CLASIFICACIÓN <i>Classification</i>	APTO PARA REGULADOR DE TENSIÓN DE RED <i>Suitable for supply voltage dimmer</i>	DATOS ADICIONALES <i>Additional data</i>
DLC 142/500-E-1 ... 10 V	220-240 V-; 0 ... 50/60 Hz	24-40 W; PF: 0,96	Stabilized current: 500 mA, at 80 V max.	75 °C	To build-in	No	Short-circuits withstand; class I; terminals connection; thermal protection at tc = 100 °C; 1-10 V dimming
DLC 142/700-E-C2-1 ... 10 V	220-240 V-; 0 ... 50/60 Hz	24-42 W; PF: 0,95	Stabilized current: 700 mA, at 60 V max.	75 °C	Indenpendent	No	Short-circuits withstand; class II; terminals connection; thermal protection at tc = 100 °C; 1-10 V dimming
DLC 142/700-E-1 ... 10 V	220-240 V-; 0 ... 50/60 Hz	24-42 W; PF: 0,95	Stabilized current: 700 mA, at 60 V max.	75 °C	To build-in	No	Short-circuits withstand; class I; terminals connection; thermal protection at tc = 100 °C; 1-10 V dimming
DLC 150/700-E-1...10 V	220-240 V-; 0 ... 50/60 Hz	31-50 W; PF: 0,96	Stabilized current: 700 mA, at 72 V max.	75 °C	To build-in	No	Short-circuits withstand; class I; terminals connection; 1-10 V dimming
DLC 150/700-1...10 V-EN-3	220-240 V-; 0 ... 50/60 Hz	31-50 W; PF: 0,96	Stabilized current: 700 mA, at 72 V max.	75 °C	To build-in	No	Short-circuits withstand; class II; terminals connection; 1-10 V dimming
DLCM 42/1200...1400-E-BT	220-240 V-; 0 ... 50/60 Hz	50 W; PF: 0,96	Stabilized current: 1200-1400 mA, at 30 V max.	80 °C	To build-in	No	Short-circuits withstand; class I; terminals connection; thermal protection at tc = 90 °C; Bluetooth dimmable
DLCM 42/1200...1400-E-C2-BT	220-240 V-; 0 ... 50/60 Hz	50 W; PF: 0,96	Stabilized current: 1200-1400 mA, at 30 V max.	80 °C	Independent	No	Short-circuits withstand; class II; terminals connection; thermal protection at tc = 90 °C; Bluetooth dimmable
DLCM 42/1200...1400-E-C2-DALI	220-240 V-; 0 ... 50/60 Hz	50 W; PF: 0,96	Stabilized current: 1200-1400 mA, at 30 V max.	80 °C	Independent	No	Short-circuits withstand; class II; terminals connection; thermal protection at tc = 90 °C; DALI dimmable
DLCM 42/1200...1400-E-DALI	220-240 V-; 0 ... 50/60 Hz	50 W; PF: 0,96	Stabilized current: 1200-1400 mA, at 30 V max.	80 °C	To build-in	No	Short-circuits withstand; class I; terminals connection; thermal protection at tc = 90 °C; DALI dimmable

Original Electrónico

AENOR INTERNACIONAL S.A.U.
Génova, 6. 28004 Madrid. España
Tel. 91 432 60 00.- www.aenor.es

Entidad de certificación de producto acreditada por ENAC con nº 01/C-PR275
Product certification body accredited by ENAC, number 01/C-PR275

AENOR

CERTIFICADO ENEC DE PRODUCTO



ANEXO I AL CERTIFICADO ENEC/000975 ANNEX I TO CERTIFICATE ENEC/000975

REFERENCIA <i>Reference</i>	TENSIÓN Y FRECUENCIA DE ALIMENTACIÓN <i>Voltage and frequency supply</i>	POTENCIA TOTAL Y FACTOR DE POTENCIA <i>Total power and power factor</i>	TENSIÓN O CORRIENTE DE SALIDA ESTABILIZADA <i>Voltage or current stabilized output</i>	TC MÁXIMA <i>Tc maximum</i>	CLASIFICACIÓN <i>Classification</i>	APTO PARA REGULADOR DE TENSIÓN DE RED <i>Suitable for supply voltage dimmer</i>	DATOS ADICIONALES <i>Additional data</i>
DLCM 48/900...1050-E-BT	220-240 V-; 0 ... 50/60 Hz	56 W; PF: 0,97	Stabilized current: 900-1050 mA, at 46 V max.	80 °C	To build-in	No	Short-circuits withstand; class I; terminals connection; thermal protection at tc = 90 °C; Bluetooth dimmable
DLCM 48/900...1050-E-C2-BT	220-240 V-; 0 ... 50/60 Hz	56 W; PF: 0,97	Stabilized current: 900-1050 mA, at 46 V max.	80 °C	Independent	No	Short-circuits withstand; class II; terminals connection; thermal protection at tc = 90 °C; Bluetooth dimmable
DLCM 48/900...1050-E-C2-DALI	220-240 V-; 0 ... 50/60 Hz	56 W; PF: 0,97	Stabilized current: 900-1050 mA, at 46 V max.	80 °C	Independent	No	Short-circuits withstand; class II; terminals connection; thermal protection at tc = 90 °C; DALI dimmable
DLCM 48/900...1050-E-DALI	220-240 V-; 0 ... 50/60 Hz	56 W; PF: 0,97	Stabilized current: 900-1050 mA, at 46 V max.	80 °C	To build-in	No	Short-circuits withstand; class I; terminals connection; thermal protection at tc = 90 °C; DALI dimmable
DLCM 50/250...350-E-BT	220-240 V-; 0 ... 50/60 Hz	58 W; PF: 0,98	Stabilized current: 250-350 mA, at 143 V max.	75 °C	To build-in	No	Short-circuits withstand; class I; terminals connection; thermal protection at tc = 85 °C; Bluetooth dimmable
DLCM 50/250...350-E-C2-BT	220-240 V-; 0 ... 50/60 Hz	58 W; PF: 0,98	Stabilized current: 250-350 mA, at 143 V max.	75 °C	Independent	No	Short-circuits withstand; class II; terminals connection; thermal protection at tc = 85 °C; Bluetooth dimmable
DLCM 50/250...350-E-C2-DALI	220-240 V-; 0 ... 50/60 Hz	58 W; PF: 0,98	Stabilized current: 250-350 mA, at 143 V max.	75 °C	Independent	No	Short-circuits withstand; class II; terminals connection; thermal protection at tc = 85 °C; DALI dimmable
DLCM 50/250...350-E-DALI	220-240 V-; 0 ... 50/60 Hz	58 W; PF: 0,98	Stabilized current: 250-350 mA, at 143 V max.	75 °C	To build-in	No	Short-circuits withstand; class I; terminals connection; thermal protection at tc = 85 °C; DALI dimmable
DLCM 50/400...500-E-BT	220-240 V-; 0 ... 50/60 Hz	58 W; PF: 0,97	Stabilized current: 400-500 mA, at 100 V max.	75 °C	To build-in	No	Short-circuits withstand; class I; terminals connection; thermal protection at tc = 85 °C; Bluetooth dimmable

Original Electrónico

AENOR INTERNACIONAL S.A.U.
Génova, 6. 28004 Madrid. España
Tel. 91 432 60 00.- www.aenor.es

Entidad de certificación de producto acreditada por ENAC con nº 01/C-PR275
Product certification body accredited by ENAC, number 01/C-PR275

CERTIFICADO ENEC DE PRODUCTO



ANEXO I AL CERTIFICADO ENEC/000975 ANNEX I TO CERTIFICATE ENEC/000975

REFERENCIA <i>Reference</i>	TENSIÓN Y FRECUENCIA DE ALIMENTACIÓN <i>Voltage and frequency supply</i>	POTENCIA TOTAL Y FACTOR DE POTENCIA <i>Total power and power factor</i>	TENSIÓN O CORRIENTE DE SALIDA ESTABILIZADA <i>Voltage or current stabilized output</i>	TC MÁXIMA <i>Tc maximum</i>	CLASIFICACIÓN <i>Classification</i>	APTO PARA REGULADOR DE TENSIÓN DE RED <i>Suitable for supply voltage dimmer</i>	DATOS ADICIONALES <i>Additional data</i>
DLCM 50/400...500-E-C2-BT	220-240 V-; 0 ... 50/60 Hz	58 W; PF: 0,97	Stabilized current: 400-500 mA, at 100 V max.	75 °C	Independent	No	Short-circuits withstand; class II; terminals connection; thermal protection at tc = 85 °C; Bluetooth dimmable
DLCM 50/400...500-E-C2-DALI	220-240 V-; 0 ... 50/60 Hz	58 W; PF: 0,97	Stabilized current: 400-500 mA, at 100 V max.	75 °C	Independent	No	Short-circuits withstand; class II; terminals connection; thermal protection at tc = 85 °C; DALI dimmable
DLCM 50/400...500-E-DALI	220-240 V-; 0 ... 50/60 Hz	58 W; PF: 0,97	Stabilized current: 400-500 mA, at 100 V max.	75 °C	To build-in	No	Short-circuits withstand; class I; terminals connection; thermal protection at tc = 85 °C; DALI dimmable
DLCM 50/600...700-E-BT	220-240 V-; 0 ... 50/60 Hz	58 W; PF: 0,97	Stabilized current: 600-700 mA, at 72 V max.	70 °C	To build-in	No	Short-circuits withstand; class I; terminals connection; thermal protection at tc = 80 °C; Bluetooth dimmable
DLCM 50/600...700-E-C2-BT	220-240 V-; 0 ... 50/60 Hz	58 W; PF: 0,97	Stabilized current: 600-700 mA, at 72 V max.	70 °C	Independent	No	Short-circuits withstand; class II; terminals connection; thermal protection at tc = 80 °C; Bluetooth dimmable
DLCM 50/600...700-E-C2-DALI	220-240 V-; 0 ... 50/60 Hz	58 W; PF: 0,97	Stabilized current: 600-700 mA, at 72 V max.	70 °C	Independent	No	Short-circuits withstand; class II; terminals connection; thermal protection at tc = 80 °C; DALI dimmable
DLCM 50/600...700-E-DALI	220-240 V-; 0 ... 50/60 Hz	58 W; PF: 0,97	Stabilized current: 600-700 mA, at 72 V max.	70 °C	To build-in	No	Short-circuits withstand; class I; terminals connection; thermal protection at tc = 80 °C; DALI dimmable
LC 137/1200-E-C2	220-240 V-; 0 ... 50/60 Hz	15-37 W; PF: 0,97	Stabilized current: 1200 mA, at 31 V max.	75 °C	Independent	No	Short-circuits withstand; class II; terminals connection; thermal protection at tc = 100 °C
LC 137/1200-E-C2-FAN	220-240 V-; 0 ... 50/60 Hz	15-37 W; PF: 0,97	Stabilized current: 1200 mA, at 31 V max.	75 °C	Independent	No	Short-circuits withstand; class II; terminals connection; thermal protection at tc = 100 °C; fan output

AENOR

CERTIFICADO ENEC DE PRODUCTO



ANEXO I AL CERTIFICADO ENEC/000975 ANNEX I TO CERTIFICATE ENEC/000975

REFERENCIA <i>Reference</i>	TENSIÓN Y FRECUENCIA DE ALIMENTACIÓN <i>Voltage and frequency supply</i>	POTENCIA TOTAL Y FACTOR DE POTENCIA <i>Total power and power factor</i>	TENSIÓN O CORRIENTE DE SALIDA ESTABILIZADA <i>Voltage or current stabilized output</i>	TC MÁXIMA <i>Tc maximum</i>	CLASIFICACIÓN <i>Classification</i>	APTO PARA REGULADOR DE TENSIÓN DE RED <i>Suitable for supply voltage dimmer</i>	DATOS ADICIONALES <i>Additional data</i>
LC 137/1200-E	220-240 V-; 0 ... 50/60 Hz	15-37 W; PF: 0,97	Stabilized current: 1200 mA, at 31 V max.	75 °C	To build-in	No	Short-circuits withstand; class I; terminals connection; thermal protection at tc = 100 °C
LC 137/1200-E-FAN	220-240 V-; 0 ... 50/60 Hz	15-37 W; PF: 0,97	Stabilized current: 1200 mA, at 31 V max.	75 °C	To build-in	No	Short-circuits withstand; class I; terminals connection; thermal protection at tc = 100 °C; fan output
LC 142/1400-E-C2	220-240 V-; 0 ... 50/60 Hz	18-42 W; PF: 0,98	Stabilized current: 1400 mA, at 30 V max.	75 °C	Independent	No	Short-circuits withstand; class II; terminals connection; thermal protection at tc = 100 °C
LC 142/1400-E-C2-FAN	220-240 V-; 0 ... 50/60 Hz	18-42 W; PF: 0,98	Stabilized current: 1400 mA, at 30 V max.	75 °C	Independent	No	Short-circuits withstand; class II; terminals connection; thermal protection at tc = 100 °C; fan output
LC 142/1400-E	220-240 V-; 0 ... 50/60 Hz	18-42 W; PF: 0,98	Stabilized current: 1400 mA, at 30 V max.	75 °C	To build-in	No	Short-circuits withstand; class I; terminals connection; thermal protection at tc = 100 °C
LC 142/1400-E-FAN	220-240 V-; 0 ... 50/60 Hz	18-42 W; PF: 0,98	Stabilized current: 1400 mA, at 30 V max.	75 °C	To build-in	No	Short-circuits withstand; class I; terminals connection; thermal protection at tc = 100 °C; fan output
LC 148/1050-E-C2	220-240 V-; 0 ... 50/60 Hz	23-48 W; PF: 0,98	Stabilized current: 1050 mA, at 46 V max.	75 °C	Independent	No	Short-circuits withstand; class II; terminals connection; thermal protection at tc = 100 °C
LC 148/1050-E-C2-FAN	220-240 V-; 0 ... 50/60 Hz	23-48 W; PF: 0,98	Stabilized current: 1050 mA, at 46 V max.	75 °C	Independent	No	Short-circuits withstand; class II; terminals connection; thermal protection at tc = 100 °C; fan output
LC 148/1050-E	220-240 V-; 0 ... 50/60 Hz	23-48 W; PF: 0,98	Stabilized current: 1050 mA, at 46 V max.	75 °C	To build-in	No	Short-circuits withstand; class I; terminals connection; thermal protection at tc = 100 °C
LC 148/1050-E-FAN	220-240 V-; 0 ... 50/60 Hz	23-48 W; PF: 0,98	Stabilized current: 1050 mA, at 46 V max.	75 °C	To build-in	No	Short-circuits withstand; class I; terminals connection; thermal protection at tc = 100 °C; fan output

Original Electrónico

AENOR INTERNACIONAL S.A.U.
Génova, 6. 28004 Madrid. España
Tel. 91 432 60 00.- www.aenor.es

Entidad de certificación de producto acreditada por ENAC con nº 01/C-PR275
Product certification body accredited by ENAC, number 01/C-PR275

AENOR

CERTIFICADO ENEC DE PRODUCTO



ANEXO I AL CERTIFICADO ENEC/000975 ANNEX I TO CERTIFICATE ENEC/000975

REFERENCIA <i>Reference</i>	TENSIÓN Y FRECUENCIA DE ALIMENTACIÓN <i>Voltage and frequency supply</i>	POTENCIA TOTAL Y FACTOR DE POTENCIA <i>Total power and power factor</i>	TENSIÓN O CORRIENTE DE SALIDA ESTABILIZADA <i>Voltage or current stabilized output</i>	TC MÁXIMA <i>Tc maximum</i>	CLASIFICACIÓN <i>Classification</i>	APTO PARA REGULADOR DE TENSIÓN DE RED <i>Suitable for supply voltage dimmer</i>	DATOS ADICIONALES <i>Additional data</i>
LC 150/350-E-C2	220-240 V-; 0 ... 50/60 Hz	23-50 W; PF: 0,98	Stabilized current: 350 mA, at 143 V max.	75 °C	Independent	No	Short-circuits withstand; class II; terminals connection; thermal protection at tc = 100 °C
LC 150/350-E-C2-FAN	220-240 V-; 0 ... 50/60 Hz	23-50 W; PF: 0,98	Stabilized current: 350 mA, at 143 V max.	75 °C	Independent	No	Short-circuits withstand; class II; terminals connection; thermal protection at tc = 100 °C; fan output
LC 150/350-E	220-240 V-; 0 ... 50/60 Hz	23-50 W; PF: 0,98	Stabilized current: 350 mA, at 143 V max.	75 °C	To build-in	No	Short-circuits withstand; class I; terminals connection; thermal protection at tc = 100 °C
LC 150/350-E-FAN	220-240 V-; 0 ... 50/60 Hz	23-50 W; PF: 0,98	Stabilized current: 350 mA, at 143 V max.	75 °C	To build-in	No	Short-circuits withstand; class I; terminals connection; thermal protection at tc = 100 °C; fan output
LC 150/500-E-C2	220-240 V-; 0 ... 50/60 Hz	23-50 W; PF: 0,98	Stabilized current: 500 mA, at 100 V max.	75 °C	Independent	No	Short-circuits withstand; class II; terminals connection; thermal protection at tc = 100 °C
LC 150/500-E-C2-FAN	220-240 V-; 0 ... 50/60 Hz	23-50 W; PF: 0,98	Stabilized current: 500 mA, at 100 V max.	75 °C	Independent	No	Short-circuits withstand; class II; terminals connection; thermal protection at tc = 100 °C; fan output
LC 150/500-E	220-240 V-; 0 ... 50/60 Hz	23-50 W; PF: 0,98	Stabilized current: 500 mA, at 100 V max.	75 °C	To build-in	No	Short-circuits withstand; class I; terminals connection; thermal protection at tc = 100 °C
LC 150/500-E-FAN	220-240 V-; 0 ... 50/60 Hz	23-50 W; PF: 0,98	Stabilized current: 500 mA, at 100 V max.	75 °C	To build-in	No	Short-circuits withstand; class I; terminals connection; thermal protection at tc = 100 °C; fan output
LC 150/700-E-C2	220-240 V-; 0 ... 50/60 Hz	24-50 W; PF: 0,98	Stabilized current: 700 mA, at 72 V max.	75 °C	Independent	No	Short-circuits withstand; class II; terminals connection; thermal protection at tc = 100 °C
LC 150/700-E-C2-FAN	220-240 V-; 0 ... 50/60 Hz	24-50 W; PF: 0,98	Stabilized current: 700 mA, at 72 V max.	75 °C	Independent	No	Short-circuits withstand; class II; terminals connection; thermal protection at tc = 100 °C; fan output

Original Electrónico

AENOR INTERNACIONAL S.A.U.
Génova, 6. 28004 Madrid. España
Tel. 91 432 60 00.- www.aenor.es

Entidad de certificación de producto acreditada por ENAC con nº 01/C-PR275
Product certification body accredited by ENAC, number 01/C-PR275

AENOR

CERTIFICADO ENEC DE PRODUCTO



ANEXO I AL CERTIFICADO ENEC/000975 ANNEX I TO CERTIFICATE ENEC/000975

REFERENCIA <i>Reference</i>	TENSIÓN Y FRECUENCIA DE ALIMENTACIÓN <i>Voltage and frequency supply</i>	POTENCIA TOTAL Y FACTOR DE POTENCIA <i>Total power and power factor</i>	TENSIÓN O CORRIENTE DE SALIDA ESTABILIZADA <i>Voltage or current stabilized output</i>	TC MÁXIMA <i>Tc maximum</i>	CLASIFICACIÓN <i>Classification</i>	APTO PARA REGULADOR DE TENSIÓN DE RED <i>Suitable for supply voltage dimmer</i>	DATOS ADICIONALES <i>Additional data</i>
LC 150/700-E	220-240 V-; 0 ... 50/60 Hz	24-50 W; PF: 0,98	Stabilized current: 700 mA, at 72 V max.	75 °C	To build-in	No	Short-circuits withstand; class I; terminals connection; thermal protection at tc = 100 °C
LC 150/700-E-FAN	220-240 V-; 0 ... 50/60 Hz	24-50 W; PF: 0,98	Stabilized current: 700 mA, at 72 V max.	75 °C	To build-in	No	Short-circuits withstand; class I; terminals connection; thermal protection at tc = 100 °C; fan output
LC 150/900-E-C2	220-240 V-; 0 ... 50/60 Hz	23-50 W; PF: 0,98	Stabilized current: 900 mA, at 55 V max.	75 °C	Independent	No	Short-circuits withstand; class II; terminals connection; thermal protection at tc = 100 °C
LC 150/900-E-C2-FAN	220-240 V-; 0 ... 50/60 Hz	23-50 W; PF: 0,98	Stabilized current: 900 mA, at 55 V max.	75 °C	Independent	No	Short-circuits withstand; class II; terminals connection; thermal protection at tc = 100 °C; fan output
LC 150/900-E	220-240 V-; 0 ... 50/60 Hz	23-50 W; PF: 0,98	Stabilized current: 900 mA, at 55 V max.	75 °C	To build-in	No	Short-circuits withstand; class I; terminals connection; thermal protection at tc = 100 °C
LC 150/900-E-FAN	220-240 V-; 0 ... 50/60 Hz	23-50 W; PF: 0,98	Stabilized current: 900 mA, at 55 V max.	75 °C	To build-in	No	Short-circuits withstand; class I; terminals connection; thermal protection at tc = 100 °C; fan output
LC 48C/1050-E-C2	230 V-; 0 ... 50/60 Hz	56 W; PF: 0,98	Stabilized current: 1050 mA; maximum output power: 26 -48 W	80 °C	Independent	No	Short-circuits withstand; class II; terminals connection; thermal protection at tc = 90 °C
LC 48C/1050-E	230 V-; 0 ... 50/60 Hz	56 W; PF: 0,98	Stabilized current: 1050 mA; maximum output power: 26 -48 W	85 °C	To build-in	No	Short-circuits withstand; class I; terminals connection; thermal protection at tc = 95 °C
LC 50C/700-E-C2	230 V-; 0 ... 50/60 Hz	59 W; PF: 0,98	Stabilized current: 700 mA; maximum output power: 26 -50 W	80 °C	Independent	No	Short-circuits withstand; class II; terminals connection; thermal protection at tc = 90 °C
LC 50C/700-E	230 V-; 0 ... 50/60 Hz	59 W; PF: 0,98	Stabilized current: 700 mA; maximum output power: 26 -50 W	85 °C	To build-in	No	Short-circuits withstand; class I; terminals connection; thermal protection at tc = 95 °C

Original Electrónico

AENOR INTERNACIONAL S.A.U.
Génova, 6. 28004 Madrid. España
Tel. 91 432 60 00.- www.aenor.es

Entidad de certificación de producto acreditada por ENAC con nº 01/C-PR275
Product certification body accredited by ENAC, number 01/C-PR275

AENOR

CERTIFICADO ENEC DE PRODUCTO



ANEXO I AL CERTIFICADO ENEC/000975 ANNEX I TO CERTIFICATE ENEC/000975

REFERENCIA <i>Reference</i>	TENSIÓN Y FRECUENCIA DE ALIMENTACIÓN <i>Voltage and frequency supply</i>	POTENCIA TOTAL Y FACTOR DE POTENCIA <i>Total power and power factor</i>	TENSIÓN O CORRIENTE DE SALIDA ESTABILIZADA <i>Voltage or current stabilized output</i>	TC MÁXIMA <i>Tc maximum</i>	CLASIFICACIÓN <i>Classification</i>	APTO PARA REGULADOR DE TENSIÓN DE RED <i>Suitable for supply voltage dimmer</i>	DATOS ADICIONALES <i>Additional data</i>
LCM 42/350 ... 1050-E-C2	220-240 V-; 0 ... 50/60 Hz	42 W; PF: 0,95	Stabilized current: 350-1050 mA, at 72 V max.	75 °C	Indenpendent	No	Short-circuits withstand; class II; terminals connection; thermal protection at tc = 100 °C; multi-current drive
LCM 42/350 ... 1050-E	220-240 V-; 0 ... 50/60 Hz	42 W; PF: 0,95	Stabilized current: 350-1050 mA, at 72 V max.	75 °C	To build-in	No	Short-circuits withstand; class I; terminals connection; thermal protection at tc = 100 °C; multi-current drive